Application No.: 10/501,7 Filing Date: July 12, 2004

Page: 2

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 1. (Currently Amended) A method for removing contaminating or undesired substances from a carrier material comprising
- a) coating an active-ingredient- containing coating onto <u>a neutralized</u> carrier material, substances within said coating penetrating into and thereby contaminating said carrier material with contaminants or other undesired substances,
 - b) drying the coated carrier material to form an active-ingredient-containing film,
- c) peeling the dried active-ingredient- containing film off the contaminated carrier material and
- d) subjecting the contaminated carrier material to a thermal treatment which comprises
- i) passing said contaminated carrier material through a thermal treatment zone at a temperature and during a period of time sufficient to remove essentially all of the contaminants or other undesired substances from the carrier material to form neutralized carrier material, and
- ii) feeding the removed contaminants or other undesired substances to a thermal afterburning using controlled air circulation, and
 - e) providing the neutralized carrier material to said coating step,

wherein said thermal treatment is performed at a temperature of approximately 80 °C and the period of time sufficient to remove essentially all of the undesired substances from the carrier material is approximately 0.5 to 6 minutes.

2. (Canceled)

Application No.: 10/501,2 Filing Date: July 12, 2004

Page: 3

3. (Original) A method according to claim 1, wherein said carrier material is paper, a polymer or a composite material composed of paper, polymer or a thin metal foil or polymer and a thin metal foil.

4. (Canceled)

- 5. (Previously Presented) A method for removing contaminating or undesired substances from a carrier material comprising
- a) coating an active-ingredient- containing coating comprising an aqueous coating composition onto carrier material, substances within said aqueous coating composition penetrating into and thereby contaminating said carrier material,
 - b) drying the coated carrier material to form an active-ingredient-containing film,
- c) peeling the dried active-ingredient- containing film off the contaminated carrier material and
 - d) subjecting the contaminated carrier material to a thermal treatment comprising
- i) passing said contaminated carrier material through a thermal treatment zone at a temperature and during a period of time sufficient to remove essentially all of the contaminants or other undesired substances from the carrier material and
- ii) feeding the removed contaminants or other undesired substances to a thermal afterburning using controlled air circulation.
- 6. (Previously Presented) A method for removing contaminating or undesired substances from a carrier material comprising
- a) coating an active-ingredient-containing coating onto carrier material, substances within said coating penetrating into and thereby contaminating said carrier material,
- b) drying the coated carrier material to form a drug-containing film, confectionary-containing film, food -containing film or cosmetics-containing film,
 - c) peeling the dried film off the contaminated carrier material and
 - d) subjecting the contaminated carrier material to a thermal treatment comprising

Application No.: 10/501,2 Filing Date: July 12, 2004

Page: 4

- i) passing said contaminated carrier material through a thermal treatment zone at a temperature and during a period of time sufficient to remove essentially all of the contaminants or other undesired substances from the carrier material and
- ii) feeding the removed contaminants or other undesired substances to a thermal afterburning using controlled air circulation.
- 7. (Previously Presented) A method according to Claim 1, said method further comprising

optionally cooling the treated carrier, and coating the treated and optionally cooled carrier, wherein said thermal treatment is imparted in a drying tunnel.

8. (New) A method according to Claim 1, wherein said thermal treatment is an infra red heat treatment.